

# Experimental determination of the rotational stiffness and moment capacity of connections in CLT buildings

Jenny Abrahamsson and Filip la Fleur




# Agenda

- Introduction and problem description
- Aim and purpose
- Experimental investigation
  - Method
  - Results
- Discussion
- Conclusions



# Introduction and problem description

- CLT – Cross laminated timber.
- Semi-rigid behavior.
- Rotational stiffness and moment capacity in connections.
- Wall-floor-wall connection.



# Motivation to the work

- Usually these connections are assumed as hinged connections
- In reality some clamping force on the wall will affect the connection in some extent
- Effects by the rotational stiffness
  - Load distribution
  - Deflection of floor
  - Dynamic behavior



# Aim and purpose

The aim with the study was to:



- Determine the rotational stiffness and moment capacity of the wall-floor-wall connection.
- Gain knowledge on how the stiffness is influenced by the thickness of the wall, the floor and the load level on the wall.

The purpose was to create a better understanding of the load-displacement behavior of a CLT connection.




# Experimental investigation: Method

- MTS 300kN load frame
- 800 mm distance between pistons
- Load level on wall: 0.5, 1.0, 1.5 and 2.0 MPa
- Relative displacement on the floor: 20 mm





Wall 140mm, floor 120mm



# Test series



- 60 test and 8 test setups
- C24 in spruce and pine
- Wall thicknesses: 80, 100 and 140 mm
- Floor thicknesses: 120 and 140 mm
- Connections:
  - Timber-timber
  - Inclined screws
  - Acoustic layers





# Results from experiments

## Influence of connection type

**Series A**




**Series B**



# Influence of connection type

## 80 mm wall


- More contribution on lower load level from the screws



# Influence of connection type


## 80 mm wall

- More contribution on lower load level from the screws
- Acoustic layer about the same difference in percentage




# Influence of connection type

140 mm wall




# Influence of connection type

140 mm wall



# Influence of connection type


140 mm wall



# Influence of connection type


## 140 mm wall

- Almost no contribution from screws on higher load




# Moment capacity influenced by the wall thickness

**0.5 MPa**




**2.0 MPa**




# Rotational stiffness influenced by the wall thickness

**0.5 MPa**




**2.0 MPa**




# Rotational stiffness influenced by the wall thickness

**1.0 MPa**




**1.5 MPa**



# Influence of connection type

## Floor variations


- Comparison between different floors
  - Spruce and pine
  - 120 and 140 mm thickness



# Influence of connection type

## Floor variations


- Comparison between different floors
  - Spruce and pine
  - 120 and 140 mm thickness



# Influence of connection type

## Floor variations


- Comparison between different floors
  - Spruce and pine
  - 120 and 140 mm thickness



# Influence of connection type

## Floor variations


- Comparison between different floors
  - Spruce and pine
  - 120 and 140 mm thickness
- Small difference in behavior



# Numerical study

Boundary condition	$u$ [mm]	$M_b$ [kNm/m]	$M_s$ [kNm/m]	$f_1$ [Hz]
Hinged	34.2	26.02	0.0	3.74
Clamped	7.6	8.66	-17.34	8.01

Model	Stories	$u$ [mm]	$M_b$ [kNm/m]	$M_s$ [kNm/m]	$f_1$ [Hz]
1	2	26.8	21.22	-4.80	4.16
2	2	27.0	21.81	-4.06	-
1	3	24.4	19.61	-6.42	4.34
2	3	24.7	19.85	-6.04	-
1	4	22.1	18.10	-7.93	4.55
2	4	22.4	18.20	-7.68	-
1	5	20.3	16.95	-9.08	4.73
2	5	20.7	16.99	-8.90	-
1	6	19.6	16.47	-9.55	4.82
2	6	19.6	16.16	-9.73	-
1	7	18.9	16.05	-9.88	4.89
2	7	18.9	15.64	-10.25	-



# Conclusions

- Wall pressure and wall thickness high influence
  - Pressure increase on 80 mm wall, from 0.5 to 1.0 MPa
    - Moment capacity increased 70 %
    - Rotational stiffness increased 30 %
  - Thickness from 80 to 140 mm
    - Moment capacity increased 200 %
    - Rotational stiffness increased 140 %



# Conclusions

- Wall pressure and wall thickness high influence
  - Pressure increase on 80 mm wall, from 0.5 to 1.0 MPa
    - Moment capacity increased 70 %
    - Rotational stiffness increased 30 %
  - Thickness from 80 to 140 mm
    - Moment capacity increased 200 %
    - Rotational stiffness increased 140 %
- Floor material and thickness low influence
  - 120 mm floor with either spruce or pine
    - Moment capacity increased 10 % for spruce
    - Rotational stiffness increased 15 % for pine



# Conclusions

- Wall pressure and wall thickness high influence
  - Pressure increase on 80 mm wall, from 0.5 to 1.0 MPa
    - Moment capacity increased 70 %
    - Rotational stiffness increased 30 %
  - Thickness from 80 to 140 mm
    - Moment capacity increased 200 %
    - Rotational stiffness increased 140 %
- Floor material and thickness low influence
  - 120 mm floor with either spruce or pine
    - Moment capacity increased 10 % for spruce
    - Rotational stiffness increased 15 % for pine
- Ductile behavior in the connection



# Thank you for listening

Thesis work:

The impact of connection stiffness on the global structural behavior in a  
CLT building: A combined experimental-numerical study

Jenny Abrahamsson and Filip la Fleur

