


Climate impact on reinforcements in wood members

Dr. Bettina Franke, Prof. Dr. Steffen Franke, Marcus Schiere

Forum Wood Building Nordic (WBN) 28-30 September 2022

Reinforcements for strengthening of cross sections

Reinforcements



www.SFS-intec.biz (12.09.2018)

restrained swelling/shrinkage




Brüninghof (2007), Dietsch et al. (2017)


Moisture content of wood

- ▶ Physical and mechanical behaviour of wood depends on the moisture content
 - ▶ Shrinkage and swelling
 - ▶ Increasing moisture content leads to decreasing of strength and stiffness properties
 - ▶ Service classes according EN 1995-1-1:2004


Reasons for structural damages



source: Frese & Blaß (2011), Dietsch & Winter (2018)




Service classes, EN 1995-1-1:2004



Timber Bridges




FE-Simulations – Moisture content, moisture induced stresses

- ▶ Simulation of seasonal climate changes for one year (meteorological station)
- ▶ Cross section width of 200 mm





FE-Modell – Moisture content, moisture induced stresses

- ▶ Simulation of climate change for riding hall
- ▶ Envelopes over the year
 - ▶ Moisture content changes within 30 - 50 mm zone
 - ▶ Moisture induced stresses over complete cross section
 - ▶ What is the impact on a reinforcement?




Climate scenarios

- ▶ Simplified sinus shaped moisture variations per year, developed from measured values




Climate scenarios





Climate scenario A








Climate scenario B



Climate scenario C








Experimental program

Climate scenario							
	unreinforced unsealed	unreinforced unsealed	unreinforced sealed	reinforced unsealed	reinforced unsealed	reinforced sealed	reinforced unsealed
[mm]	160/160/600	160/320/600	160/320/600	160/160/600	160/320/600	160/320/600	160/320/600
A	# P9	# P10	# P23	# P1	# P2 ¹⁾	# P3 ¹⁾ , P11 ¹⁾ , P12	# P4
B			# P25	-	-	# P15 ²⁾ , P16	-
C			# P27	# P5	# P6 ¹⁾	# P7 ¹⁾ , P19 ¹⁾ , P20	# P8




¹⁾ Measurement of moisture content in depths of 15 and 40 mm

²⁾ Measurement of moisture content in depths of 15, 25, and 40 mm





Measuring techniques

Measurand	Displacement (global)	Displacement (local)	Moisture content	Strain (local)
Methode	Dial gauge	Deformeter	Electrical resistance	Strain gauges
Range/ Position	670, 1070 mm	100, 200 mm	15, 25, 40 mm	290 mm depth
Accuracy	0.01 mm	0.001 mm	1-2 M%	Micro strain
Photo				
Principal Sketch				

Preparation of test examples




Results – Moisture content at the specimens




Results – Moisture content at the specimens


Climate scenario A




Climate scenario B




Climate scenario C




Climate scenario A - unsealed







Climate scenario B - sealed




Climate scenario C - unsealed




Results – Calculated average moisture content over the depth




Results – Deformation and strains of the reinforcements







Climate scenario A




Climate scenario B




Climate scenario C




Results - Deformation and strains on wood surface




Climate scenario A




Climate scenario B




Climate scenario C




Climate scenario A - unsealed




Climate scenario A - sealed




Climate scenario B - sealed




Climate scenario C - unsealed




Climate scenario C - sealed



Results – Characterization of the effect of reinforcements



Results – Characterization of the effect of reinforcements




$$\gamma = \frac{A_1 E_1}{A_1 E_1 + A_2 E_2}$$

$$\Delta \varepsilon = \Delta \sigma / E + \alpha \Delta u. \quad (3)$$

$$\Delta \varepsilon_0 = (F_e + \alpha_1 \Delta u_1 A_1 E_1) / (A_1 E_1 + A_2 E_2). \quad (4)$$



$$\begin{aligned} \Delta \sigma_1 &= ((F_e + \alpha_1 \Delta u_1 A_1 E_1) / (A_1 E_1 + A_2 E_2) - \alpha_1 \Delta u_1) E_1 \\ \Delta \sigma_2 &= (F_e + \alpha_1 \Delta u_1 A_1 E_1) / (A_1 E_1 + A_2 E_2) E_2 \end{aligned} \quad (5)$$

$$\Delta \sigma_1 = \alpha_1 \Delta u_1 (\gamma - 1) E_1 \text{ and } \Delta \sigma_2 = \alpha_1 \Delta u_1 \gamma E_2. \quad (6)$$




Conclusion and recommendations

- ▶ Experimental test series successfully carried out
 - ▶ Realistic values observed for moisture content, displacement and strains
 - ▶ Effective hygro-expansion coefficients calculated $\alpha_{\text{eff, reinf}} = 0.05 \text{ \%}/M\%$
 - ▶ $\alpha_{\text{eff, reinf}}$ includes effects of mechanosorptive relaxation and time dependent creep under the presence of reinforcement
-
- ▶ Theoretical hygroexpansion coefficient of wood perp. to grain lie around $\alpha_{\text{r,t}} = 0.25 \text{ \%}/M\%$
 - ▶ Therefore, larger moisture content impacts are possible without cracking
-
- ▶ Next steps: calculating the forces within the reinforcement during climate exposure
 - ▶ Research report will be available by end of the year



Project – Funding, Partners, Experts

- ▶ Funding by Federal Office of Environmental FOEN Switzerland
- ▶ Duration of 24 months
- ▶ Research report will be available soon



<https://www.bfh.ch/de/forschung/forschungsprojekte/2019-719-067-285/>

Thank you for your attention!

Dr. Bettina Franke, Prof. Dr. Steffen Franke

bettina.franke@bfh.ch

steffen.franke@bfh.ch

www.ahb.bfh.ch

