

FORUM
HOLZBAU
INTERNATIONAL

hob

LIGNOALP®

CityWave

MILANO

Ing. Claudio Bertagnolli

Citylife - Mailand



Citylife - Mailand


Citywave

Arch. BIG


Bjarke Ingels




Das Bauwerk




Werdegang Struktur Canopy






Varianten Studie










CANOPY
CANOPY BUILD-UP AND STRUCTURAL PRINCIPLE




Canopy Hauptstruktur Kabel + Holzschale





Top view – cable arrangement with straight cables in plane







5 Layers clt panels
+
cables in between




Typical connections

between panels



along borders



along cables



Canopy
Hauptstruktur:
Kabel + Holzschale




Laborversuche an der Uni TN


Lastproben
Steifigkeit
Dämpfungskontante





Laborversuche

Windkanaltests






FINS Schwingungsdämpfer oder Regenabflüsse



Delivery parts GERB



Stand der Arbeiten





Kennzahlen

Dachfläche Canopy

4.500 m²

Spannkabel nur Canopy

ca. 50 to

Holzmenge

1.800 m³

Anzahl Schrauben

ca. 400.000

DANKE

Ing. Claudio Bertagnoli

FORUM
HOLZBAU
INTERNATIONAL

ho

LIGNOALP®
DAMIANI-HOLZ&KO AG

CityWave

MILANO


Ing. Francesco Marroni

Parametric to Constructive Design Approach

The Wave – Timber Canopy

1. Parametric System Recognition

- Identification of the canopy as a parametric architectural system
- Top-down holistic workflow: Concept → Coordination → Detail
- 360° assessment prevents early-stage design drift










Parametric to Constructive Design Approach

The Wave – Timber Canopy

2. From Executive to Constructive Design

- Implementation of fastening rules and CLT base panels
- Double-curved geometry translated into manufacturable elements
- Integration of production constraints and site installation logic




Parametric to Constructive Design Approach

The Wave – Timber Canopy






3. Timber System Optimization

- Manufacturing speed and workflow refinement
- Tolerance strategy for intersecting geometries
- Iterative segmentation of layers aligned with assembly constraints





4. Detail Design Phase

- Final tuning of construction elements
- Structural–production–installation integration
- Predictable costs, timing, and accuracy



5. Installation Logic Shift



- Discovery: temporary support structure becomes primary geometric reference
- Inversion of the installation sequence
- Early-stage precision enables orientation on 4350 m² open square



Parametric to Constructive Design Approach

The Wave – Timber Canopy



5. Installation Logic Shift





KEY DRIVERS

- Holistic DMFA workflow linking geometry to construction
- Double-curvature requires parametric-constructive integration: geometry-to-construction integration
- Interdisciplinary coordination
- Iterative optimization of tolerances and connections to define Segmentation
- Installation-driven design: design reshaped entire workflow
- Water & moisture control as a critical success factor







KEY DRIVERS








- Holistic DMFA workflow linking geometry to construction
- Double-curvature requires parametric-constructive integration: geometry-to-construction integration
- Interdisciplinary coordination
- Iterative optimization of tolerances and connections to define Segmentation
- Installation-driven design: design reshaped entire workflow
- Water & moisture control as a critical success factor



KEY DRIVERS

- Holistic DMFA workflow linking geometry to construction
- Double-curvature requires parametric-constructive integration: geometry-to-construction integration
- **Interdisciplinary coordination**
- Iterative optimization of tolerances and connections to define Segmentation
- Installation-driven design: design reshaped entire workflow
- Water & moisture control as a critical success factor





- In each layer one or more segmentation areas can exist
- each segmentation area defines an area in which the segmentation follows a segmentation direction and width
- The segmentation area name consists of <LayerNumber>-<SegmentationAreaLetter>

- In each layer one or more segmentation areas can exist
- each segmentation area defines an area in which the segmentation follows a segmentation direction and width
- The segmentation area name consists of <LayerNumber>-<SegmentationAreaLetter>

- In each layer one or more segmentation areas can exist
- each segmentation area defines an area in which the segmentation follows a segmentation direction and width
- The segmentation area name consists of <LayerNumber>-<SegmentationAreaLetter>

- In each layer one or more segmentation areas can exist
- each segmentation area defines an area in which the segmentation follows a segmentation direction and width
- The segmentation area name consists of <LayerNumber>-<SegmentationAreaLetter>
- The letter is named from A to Z

KEY DRIVERS

- Holistic DMFA workflow linking geometry to construction
- Double-curvature requires parametric-constructive integration: geometry-to-construction integration
- Interdisciplinary coordination
- Iterative optimization of tolerances and connections to define Segmentation
- Installation-driven design: design reshaped entire workflow
- Water & moisture control as a critical success factor




KEY DRIVERS

- Holistic DMFA workflow linking geometry to construction
- Double-curvature requires parametric-constructive integration: geometry-to-construction integration
- Interdisciplinary coordination
- Iterative optimization of tolerances and connections to define Segmentation
- Installation-driven design: design reshaped entire workflow
- Water & moisture control as a critical success factor





KEY DRIVERS

- Holistic DMFA workflow linking geometry to construction
- Double-curvature requires parametric-constructive integration: geometry-to-construction integration
- Interdisciplinary coordination
- Iterative optimization of tolerances and connections to define Segmentation
- Installation-driven design: design reshaped entire workflow
- Water & moisture control as a critical success factor




INSTALLATION KEY MOMENTS









INSTALLATION KEY MOMENTS



INSTALLATION KEY MOMENTS







Thank you
Ing. Francesco Marroni